

LINEAR TECHNOLOGY MATERIALS DECLARATION

1tc2992cms#trpbf

(Engineering Calculation)

MSOP

(printed on: 2020-07-11 22:12:38)

TOTAL MASS (g) : 0.039116

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.003723 | 1000000 | 95178.3828125 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.013845 | 975000 | 353947 | | |
| | | Iron (Fe) | 7439-89-6 | 0.000355 | 25000 | 9075.56445312 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000004 | 300 | 102.259880066 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000010 | 700 | 255.649703979 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.014214 | 1001000 | 363380.46875 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.000710 | 1000000 | 18151.7675781 | | |
| | | External Plating Total: | | | | 0.000710 | 1000000 | 18151.7675781 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000086 | 1000000 | 2198.58740234 | | |
| Internal Plating Total: | | | | 0.000086 | 1000000 | 2198.58740234 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.001082 | 750000 | 27661.296875 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000361 | 250000 | 9228.95410156 | | |
| Die Attach Total: | | | | 0.001443 | 1000000 | 36890.2539062 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.002533 | 135000 | 64756.0664062 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.016134 | 860000 | 412465.21875 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000094 | 5000 | 2403.10717773 | | |
| | | Encapsulation Total: | | | | 0.018761 | 1000000 | 479624.375 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000179 | 1000000 | 4576.12939453 | | |
| | | | | | TOTAL MASS (g) : | 0.039116 | | |