

## Specification Sheet

Part Number: 151-10914



Q Tie Mount with Adhesive, 0.79" x 0.79" x 0.17", 4 way entry for Q18 - Q30 ties, PA66, Black, 100/bag

<b>Article Number</b>	151-10914
<b>Type</b>	QM20A
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• 2- or 4-way entry options for the Q Tie, offering flexibility and stability</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Q Mounts are designed to work exclusively with the Q Tie cable tie series. This mounting component is available with adhesive or can be secured with screws. The Q Mount allows either a 2- or 4-way entry for the Q Tie, providing a quick and simple insertion into the mount. Once in place, the Q Tie will not slip out, even in vertical mounting applications.
<b>Short Description</b>	Q Tie Mount with Adhesive, 0.79" x 0.79" x 0.17", 4 way entry for Q18 - Q30 ties, PA66, Black, 100/bag

**Global Part Name**

QM20A-PA66-BK

**Length L (Imperial)**

0.79

**Length L (Metric)**

20.0

**Fixation Method**

Screw Mounting and Adhesive

**Width W (Imperial)**

0.79

**Width W (Metric)**

20.0

**Height H (Imperial)**

0.17

**Height H (Metric)**

3.7

**Cable Tie Width Max (Imperial)**

0.14

**Cable Tie Width Max (Metric)**

4.0

**Mounting Hole Diameter D (Imperial)**

0.12

**Mounting Hole Diameter D (Metric)**

3.1 mm

**Mounting Hole Diameter D Min (Imperial)**

0.12

**Mounting Hole Diameter D Max (Metric)**

3.1

**Mounting Hole Centers (Imperial)**

0.53

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Adhesive</b>	Synthetic rubber with base of polyethylene foam
<b>Flammability</b>	UL 94 V2 (excluding adhesive)
<b>Halogen free</b>	Yes
<b>Adhesive Operating Temperature</b>	-40°F to +140°F (-40°C to +60°C)
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.