


ACR08B333JGS

ACR Indust COG HT200C, Ceramic, 0.033 uF, 5%, 50 VDC, COG, Commercial, High Temperature, Lead Spacing = 10.16mm



Dimensions	
L	12.7mm MAX
W	12.7mm MAX
Т	2.54mm MAX
S	10.16mm +/-0.38mm
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1

General Information		
Series	ACR Indust COG HT200C	
Style	Radial	
Description	Commercial, High Temperature	
Features	Commercial	
RoHS	No	
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	f2ec9c71-d741-45f9-8d01-f6de6baf235a	
Termination	Gold	
Failure Rate	N/A	
Testing and Reliability	Standard	
AEC-Q200	No	

Specifications				
Capacitance	0.033 uF			
Capacitance Tolerance	5%			
Voltage DC	50 VDC			
Dielectric Withstanding Voltage	125 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	COG			
Dissipation Factor	0.15% 1 kHz 1.0Vrms			
Insulation Resistance	30.303 GOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.