


## M4(100)-240X50MT0800

Aliases (UFSM40010CT080)

KEMET, M4, Flex Suppressors, RFID

General Information



Series M4
Style Sheet
Description Flex Suppressor Halogen Free Type
Features High Magnetic Permeability Type, Low Magnetic Loss Type
RoHS Yes
Qualifications UL94 HB, UL File No. E176124
Environment Halogen Free, PVC Free, Lead Free, Red Phosphorus Free

Specifications

Temperature Range -40/+105°C

Permeability 40 u At 13.56MHz

Effective Frequency 13.56 MHz and below

Specific Gravity 3.1 TYP

Surface Resistivity 10 MOhm/sq. TYP

Click here for the 3D model.

Dimensions		
Sheet Size	240mmx50M	
L	50000mm NOM	
W	240mm NOM	
Т	0.1mm NOM	

Packaging Specifications	
Tape Description	Without PET Tape (Txx00)
Tape Thickness	0.03mm
Component Weight	3966.67 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.