


TD1150 SERIES DETECTOR SWITCH

ANTI-VANDAL SWITCHES
 DETECTOR SWITCHES
 DIP SWITCHES
 KEYLOCK SWITCHES
 NAVIGATION SWITCHES
 PUSHBUTTON SWITCHES
 ROCKER SWITCHES
 ROTARY SWITCHES
 SLIDE SWITCHES
 SNAP ACTION SWITCHES
 TACTILE SWITCHES
 TOGGLE SWITCHES
 CAP OPTIONS



APPLICATIONS / MARKETS



RoHS

SPECIFICATIONS

Contact Rating: 100mA @ 12VDC
Contact Resistance: 500 mΩ
Contact Arrangement: SPST N.O.
Insulation Resistance: 100 MΩ Min. @ 500VDC
Dielectric Strength: 500VAC per minute
Electrical Life: 300,000 Cycles
Operating/Storage Temperature: -40°C to 85°C
Travel: 1.15mm
Moisture Protection: IP67
Actuator Force: 35gf nominal to electrical make
 100gf max travel to full stroke

FEATURES & BENEFITS

- Compact size
- IP67 ingress protection
- PCB terminal type

PART NUMBER CONFIGURATOR

Series	Acuator	Actuator Force	Contact Material
<input type="text" value="TD1150"/>	<input type="text" value="A - 11.6 [0.46 in]"/>	<input type="text" value="F100 - 100gf"/>	<input type="text" value="Q - Silver"/>

Specifications subject to change without notice 6.12.2019



E-SWITCH®

www.e-switch.com

800.867.2717

1

TD1150 SERIES DETECTOR SWITCH

BODY DIMENSIONS

