

Specification Sheet

Part Number: 558-00345



Article Number	558-00345
Туре	HT3WH250
Color	White (WH)
Features & Benefits	• Pre-printed header striped continuous vinyl rolls come in different header colors, providing a variety of printing options. • The headers can be printed with various ARC FLASH, WARNING And CAUTION headlines to meet OSHA safety standards for identifying electrical panels and equipment. • Signs can be designed in Tagprint Pro labeling software and printed with any HellermannTyton thermal transfer printing system with optional cutter attached.
Quantity Per	roll

Product Description

Continuous Vinyl Labels are made with UV-stable materials for long outdoor life. The labels are extruded in the actual color and not colored using surface inks for long-term fade resistance. Vinyl labels are provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems. Good for all surface types except powder coat painted or low surface energy substrates such as polyproylene. Test on these surfaces before approving.

Short Description	Adhesive Labels, Solid Color Continuous Roll, 3.0" x 250', VL, White, 250 ft/roll
Global Part Name	HT3WH250-V-WH
Technical Description	Solid Colored Continuous Roll, 3.0" X 250', Vinyl, White
Length L (Imperial)	250.0
Length L (Metric)	76.20
Variant	3.2mil, 50lb bleached kraft paper
Width W (Imperial)	3.0
Width W (Metric)	76.2
Thickness T (Metric)	64.0
Width of Liner (Metric)	76.2
Width of Liner (imperial)	3.0
Material	Vinyl
Material Shortcut	V
Adhesive	Acrylic
Halogen free	No

UV Resistant (Yes/No)	Yes
Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
Operating Temperature (Metric)	-40°F to +180°F (-40°C to +82°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 969
UL Recognized (US)	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.68
Weight (Imperial)	1.48

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions