[	т Q т т		0	₩   >	>	7
4						4
ω			LAYOUT SHOWN AS EXA	AMPLE		3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension					
	-Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
2	-Shell Material   : Aluminium   ØS   29.4 Max     -Shell Plating   : Olive drab Cadmium   Z   31 Max     -Shell Plating   : Olive drab Cadmium   VV THREAD   M18x1-6g     -Insulator   : Thermoplastic   VV THREAD   M18x1-6g     -Contacts   : Copper Alloy   -   -     -Seals & Grommet   : Silicon Elastomer   -   -     -Contact Plating   : Gold over copper Alloy 0.8µm minimum   -   -	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D513W03PN				2
	-Contact Plating   : Gold over copper Alloy 0.8μm minimum     -Durability   : 500 Mating cycles     -Delivered with Souriau contacts and Accessories					2
	-Temperature Range - 65°C to +175°C	A 18-10-2016	First Release			-
	-Salt Spray : 500 hours					_
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	-
		TITLE	Aluminium Plug 8D series			
_ <b>_</b>	BASIC SERIES: 8D 5 - 13 W 03 P N   SHELL TYPE : Plug with RFI Shielding	SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>		-
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : N	it must not be reproduce				
	SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matings)	FORMAT		communicated without		
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 13-03	FORMAT A3	SOURIAU I		SHEET	
1			8D513W0		1/2	1

	т	۵	н <b>г</b>	т	D	C	
		Contact Layout					
4							
	Ctc A B C	3#16 13-03 X Y 2.39 1.47 0 -2.79 -2.39 1.47					
ω							
-	-						
						SOURIAU shall not b due to a use of th the Specifications issue (professional	e Products v ed by either
N							Coun FR
						PN:	8D513
					A 18-10-201 ISS DATE Designed By:	L6 First Release Latest modification - b Date:	у
					TITLE		Alumi
<u> </u>					SCALE NA		General linear Tolerances: ±
					SOURIAL	J WWW.SO	URIAU.
					FORMAT	S	OURIA

G

Н

F

Е

A3

D

С

