	<b>エ</b>	۵	н <b>г</b>		т	D	0	σ	A	]
4		M Thread	ØS							
ယ							LAYOUT SHOWN	AS EXAMPLE		
			Keying S	Shown as example						
CHARACT	ERISTICS				tor dimension					
-Standard	: Based on MIL-DTL-	89999 Series III		Dim	Nominal					
-Shell Plati -Insulator -Contacts						SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Gr -Contact Pl		n Elastomer over copper Alloy 0.8µm m	ninimum				Co		n & Control List t Listed	
-Durability		Nating cycles					PN: 8D5			
-Temperat	-	C to +175°C				A 19-10-20	16 First Release			
-Salt Spray —— -Mass		iours g ± 10%				ISS DATE Designed By:		cu	STOMER DRAWING	MOD N°
						TITLE	Alu	minium Plug 8D se	eries	
BASIC SERI	ES: E : Plug with RFI Sh		13 Z 08 S	E		SCALE	General line Tolerance		NPRDS / PROJECT 859	
	CONTACT TYPE : Standard Crimp Contact   SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings)						SOURIAU     This document is the property of SOURIAU       it must not be reproduced or communicated without permission			or
	: Z = Black Zir	nc Nickel		001	CONTACT LAYOUT : 13-08	FORMAT		AU DRG N°		SHEET
						A3		3Z08SE-C		1/2
						1.5	XII5	<u> </u>		1/2 1

		G	гт —	m		0
		Contact Layout				
4		$X \begin{pmatrix} G \\ \oplus \\$				
		Contacts (Insert arrangement 13-8)       Contact location       X-axis (mm)       Vanis (mm)       A     +.065 (1.65)     +.157 (3.99)       B     +.170 (4.32)     +.000 (0.00)       C     +.120 (3.05)    120 (3.05)       D     ·.000 (0.00)    170 (4.32)       E    120 (3.05)    120 (3.05)       F    170 (4.32)     +.000 (0.00)       G    065 (1.65)     +.157 (3.99)       H     +.000 (0.00)     +.044 (1.12)				
ယ	Shell Arrangement Nu size no. cr 13 -8	umber of Size Service Contact Supersede ontacts contacts rating location 8 20 I All MS20051-4				
	_				[	SOURIAU shall not be liable for an
						due to a use of the Products wl the Specifications issued by either o (professional recommenda
N						Counti FR PN: 8D513
					A 19-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					SCALE	General linear Tolerances:
<b>_</b>					SOURIA	
					FORMAT A3	SOURIAU 8D513Z
	Н	G	F	E	D	C

