


PMZ2035RE6100K150R06

Aliases (P435EJ104K440CH151)

PMZ2035/P435, Film, Metallized Paper, Resistor/Capacitor, 0.1 uF, 10%, 1000 VDC, 85°C, Lead Spacing = 25.4mm



Click here for the 3D model.

Dimensions	,
L	30.5mm MAX
Н	19mm MAX
Т	12.1mm MAX
S	25.4mm +/-0.4mm
LL	6mm -1mm
F	1mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	800

General Information	
Series	PMZ2035/P435
Dielectric	Metallized Paper
Style	Radial
Features	RC Unit approved
RoHS	Yes
Lead	Wire Leads
Qualifications	ENEC
AEC-Q200	No
Construction	Molded
Component Weight	10 g
Miscellaneous	Resistor Tolerance: +/-30%. Resistor= 150 Ohms.

Specifications	
Capacitance	0.1 uF
Capacitance Tolerance	10%
Voltage AC	440 VAC
Voltage DC	1000 VDC
Temperature Range	-40/+85°C
Rated Temperature	85°C
Insulation Resistance	6 GOhms
Safety Class	X1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.