



Mallory Sonalert Products, Inc.

Part #:

ZT028LAIC1R

Sales Outline Drawing

Revision:

C

Specifications:

INDIVIDUAL CONTROL OF LIGHT AND SOUND

| Function | LIGHT | SOUND |
|-----------------------|---|-------------------------|
| Sound Level Category | N/A | Loud |
| Mode of Operation | Continuous | Continuous |
| Lens Color | Opaque White | N/A |
| LED Color | RED | N/A |
| Rated Voltage | 12 VDC | 12 VDC |
| Voltage Range | 20 to 28 VAC/DC | 20 to 28 VAC/DC |
| Power Connection | L+ to +Vdc & L- to -Vdc | S+ to +Vdc & S- to -Vdc |
| Current Draw | 25mA MAX | 25mA MAX |
| Frequency | N/A | 3900 ± 500 Hz |
| Loudness @ 2 FT | N/A | 85 to 95 dB(A) Typ. |
| Housing Material | 6/6 Nylon, Color: Black | |
| Front Cap Material | 6/6 Nylon, Color: Opaque White | |
| Storage Temperature | -40° to +80° C | |
| Operating Temperature | -30° to +65° C | |
| Panel Mounting | Recommended hole size is 22.5 mm. Thread front will fit standard 22.5mm hole. | |
| Knurled Nut | Used to attach part to panel. The max recommended torque is 10 in-lbs. | |
| Weight (Typical) | 28 g | |
| NEMA 3R,4X, & 12 | Approved with use of included gasket. | |
| Options | Please contact factory. | |

Dimensions: Inches (mm)

cUL Recognized

ROHS Compliant

PATENT NUMBER

9165440

