

Revision Number: 007.0 Issue date: 11/30/2017

1. PRODUCT AND COMPANY IDENTIFICATION

 Product name:
 LOCTITE 3616 300CC CQ
 IDH number:
 244565

 Product type:
 One-part epoxy
 Item number:
 29848

 Restriction of Use:
 None identified
 Region:
 United State

Restriction of Use: None identified Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Region: United States **Contact information:**

Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2





Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	40 - 50
Limestone	1317-65-3	10 - 20
4,4'-(1-Methylethylidene) bisphenol reaction products with (Chloromethyl) oxirane, 2-methyl-1H-imidazole, (phenoxymethyl) oxirane, p	134091-76-2	10 - 20
2,3-Epoxypropyl neodecanoate	26761-45-5	5 - 10
Silica, amorphous, fumed, crystal-free	112945-52-5	5 - 10
Treated fumed silica	67762-90-7	1 - 5
Phenol polymer with formaldehyde, glycidyl ether	28064-14-4	1 - 5
Calcium 4-[(5-chloro-4-methyl-2- sulphonatophenyl)azo]-3-hydroxy-2- naphthoate	7023-61-2	0.1 - 1
4,4'-Isopropylidenediphenol	80-05-7	0.1 - 1
4,4'-Methylenediphenol, polymer with 1-chloro-2,3-epoxypropane	42423-25-6	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before

reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If symptoms develop

and persist, get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Calcium oxide. Toxic and irritating

vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand,

silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls /

Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
4,4'-(1-Methylethylidene) bisphenol reaction products with (Chloromethyl) oxirane, 2-methyl-1H-imidazole, (phenoxymethyl) oxirane, p	None	None	None	None
2,3-Epoxypropyl neodecanoate	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Phenol polymer with formaldehyde, glycidyl ether	None	None	None	None
Calcium 4-[(5-chloro-4-methyl-2- sulphonatophenyl)azo]-3-hydroxy-2- naphthoate	None	None	None	None
4,4'-Isopropylidenediphenol	None	None	None	None
4,4'-Methylenediphenol, polymer with 1-chloro-2,3-epoxypropane	None	None	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

imits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Red
Odor: mild

Odor threshold:

pH:

Not available.

Not determined

Vapor pressure: < 1.0 mm hg (20 °C (68°F))

Boiling point/range: Not available.

Melting point/ range: Not determined

Specific gravity: 1.33

Vapor density: Not determined

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower: Not determined Flammable/Explosive limits - upper: Not determined Autoignition temperature: Not determined Flammability: Not applicable Not determined **Evaporation rate:** Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. **VOC** content: Not available. Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Oxides of nitrogen. Calcium oxide. Irritating vapors.

Incompatible materials: Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, and strong

mineral and organic bases, especially primary and secondary aliphatic amines. Mercaptans.

Fluorine. Aluminum. Ammonium salts.

Reactivity: Not available.

Conditions to avoid: Store away from incompatible materials. Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation.

Skin contact:

Causes skin irritation. May cause allergic skin reaction. Repeated or prolonged contact can result in drying of skin. Contact at elevated temperatures may cause thermal burns. Causes serious eye irritation. Contact at elevated temperatures may cause thermal burns.

Eye contact:

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant	
Limestone	None	Nuisance dust	
4,4'-(1-Methylethylidene) bisphenol reaction products with (Chloromethyl) oxirane, 2-methyl-1H-imidazole, (phenoxymethyl) oxirane, p	None	No Records	
2,3-Epoxypropyl neodecanoate	None	Irritant, Allergen	
Silica, amorphous, fumed, crystal-free	None	Nuisance dust	
Treated fumed silica	None	Irritant	
Phenol polymer with formaldehyde, glycidyl ether	None	Allergen, Irritant	
Calcium 4-[(5-chloro-4-methyl-2- sulphonatophenyl)azo]-3-hydroxy-2- naphthoate	None	No Target Organs	
4,4'-lsopropylidenediphenol	Oral LD50 (Rat) = 4,100 mg/kg Oral LD50 (Rat) = 3,300 mg/kg Oral LD50 (Mouse) = 5,280 mg/kg Oral LD50 (Mouse) = 2,500 mg/kg Oral LD50 (Mouse) = 4,100 mg/kg	Allergen, Blood, Irritant, Kidney, Reproductive, Spleen	
4,4'-Methylenediphenol, polymer with 1-chloro-2,3-epoxypropane	None	No Data	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Limestone	No	No	No
4,4'-(1-Methylethylidene) bisphenol reaction products with (Chloromethyl) oxirane, 2-methyl-1H-imidazole, (phenoxymethyl) oxirane, p	No	No	No
2,3-Epoxypropyl neodecanoate	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Treated fumed silica	No	No	No
Phenol polymer with formaldehyde, glycidyl ether	No	No	No
Calcium 4-[(5-chloro-4-methyl-2- sulphonatophenyl)azo]-3-hydroxy-2- naphthoate	No	No	No
4,4'-Isopropylidenediphenol	No	No	No
4,4'-Methylenediphenol, polymer with 1-chloro-2,3-epoxypropane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

Product name: LOCTITE 3616 300CC CQ IDH number: 244565

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated (Up to 300 ml max per inner/primary package when shipped as

originally packaged only)

Hazard class or division:
Identification number:
Packing group:
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin

resin) (Up to 300 ml max per inner/primary package when shipped as originally

packaged only)

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A

Epichlorhydrin resin) (Up to 300 ml max per inner/primary package when shipped

as originally packaged only)

Hazard class or division:

Identification number: UN 3082

Packing group:

Marine pollutant: Bisphenol-A Epichlorhydrin resin

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

IDH number: 244565 Product name: LOCTITE 3616 300CC CQ

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/30/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.