	Ξ		G		п		т		t			0		Φ		Þ		
4			V Thread	ØS														4
ω	•				~~+	-t						LAYC	OUT SHOWN AS E	EXAMPLE				3
					Keying Sh	nown as examp	ole											
CH#	ARACTERISTICS					C	Connector dir	mension										
-	tandard : Based on N		eries III			Di		Nominal 25 Max										
-She -Insu -Con -Sea	hell Material hell Plating nsulator ontacts eals & Grommet	: Aluminium : Olive drab C : Thermoplas : Copper Allor : Silicon Elast	ic , omer				<u>Z</u>	31 Max M15x1-6g				the Specifications is	f the Products w ssued by either c	hich does not con of the Parties or b ation, technical no rry Jurisd	mply with by a third party	List		2
-Con	ontact Plating urability elivered without Sou	: 500 Mating	pper Alloy 0.8µm n cycles	Immum								PN	l: 8D511V		Not Listed			
-Ten	emperature Range	: -65℃ to +1	′5°C						[Α	17-10-2016	First Release						
	alt Spray	: 500 hours	n/						ŀ	ISS	DATE	Latest modification	- by			NA	10D N°	
	1855	: 14.13 g ± 10	/0							Designed		Date:	5 y		CUSTOMER DE			
								Т	TITLE	Aluminium Plug 8D series								
	ASIC SERIES:		8D 5 -	11 W	05 P	EL		Delivered W/O 0	Contacts	SCAL			General linear Tolerances: ±		NPRDS / PR 859			1
CON	CONTACT TYPE : Standard Crimp Contact ORIENT				TION : E			J WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or										
	IELL SIZE : 11						CONTA	CT TYPE : PIN(500 N		FORM	AT				communicate	ed without permissio		
	ATING : W =	Olive drab Cadr	nium					CONTACT LAYOUT	T:11-05	A3			SOURIAU 8D511W				SHEET 1/2	
													0111 1 1 1 1 1				1//	

r	т	G	וד	m		0	
		Contact Layout					
4	-×_	$ \begin{array}{c} & & \\ & & \\ & \\ & \\ & \\ & \\ & \\ & \\ & $					
		X-axis Y-axis (mm) +.065 (165) +.056 (142) +.113 (2.87) 065 (1.65) +.000 (0.00) 130 (3.30) 113 (2.87) 065 (1.65) 065 (1.65) +.056 (1.42) ber of Size Service Contact Supersedes tacts contacts rating location Supersedes					
ω	11 -5 5	5 20 I Ali MS20050-5					
	-					SOURIAU shall not be liable due to a use of the Produ the Specifications issued by ei (professional recomm	ucts w ither c
N						PN: 8D52	Count FR 11V
_					A 17-10-20 ISS DATE Designed By:	016 First Release	
					SCALE	Alu General li Tolerand	
-					NA SOURIA		
				_	FORMAT A3	SOUR 8D512	
L	Н	G	F	E	D	C	

	Β			А				
							4	
							3	
which r of th datior ntry R	on-conformit n does not co ne Parties or k n, technical no Jurisd	mply wit by a thiro otice.)	th d party Control Lis	t			2	
		CUST	OMER DRA	WING	N	10D N°	╞	
customer drawing iinium Plug 8D series								
r		NPI	RDS / PROJ 859	ECI			1	
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission								
UC	DRG N°	<u> </u>				SHEET	1	
V05	5PEL-C					2/2		
	В			А				