ב   ס   	т <u>п</u>		0		
			LAYOUT SHOWN AS EXAM	PLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension				
-Standard : Based on MIL-DTL-38999 Series III	DimNominalØS35.7 Max				
-Shell Material : Aluminium	Z 31 Max		SOURIAU shall not be liable for any nor		
-Shell Plating : Nickel -Insulator : Thermoplastic	VV THREAD M25x1-6g	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party			
-Insulator : Thermoplastic -Contacts : Copper Alloy			(professional recommendation,		
-Seals & Grommet : Silicon Elastomer		L	Country	Jurisdiction & Control List	]
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	Not Listed	_
-Durability : 500 Mating cycles					
-Delivered with Souriau contacts and Accessories		PN: 8D517F20PN			
-Temperature Range : -65°C to +200°C		A 14-10-2016 Fi	rst Release		
-Salt Spray : 48 hours					
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		TITLE			
		SCALE			
BASIC SERIES: 8D 5 - 17 F 20	P N		General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
SHELL TYPE : Plug with RFI Shielding		NA NA		This document is the pro	operty of
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	SOURIAU	WWW.SOURIAU.CON	COUDIAL	
SHELL SIZE : 17	CONTACT TYPE : PIN(500 Matings)	1		communicated without p	
PLATING : F = Nickel	CONTACT LAYOUT : 17-20		SOURIAU DI	RG N°	SHEET
· · · · ·		A3	8D517F20F		1/2

4	(	Contact Layout 20* 4#12 16#22D				
دى	Ctc A B C D 1 2 3 4 5 6 7 8 9 10	17-20   X Y   0 5.51   3.17 0   0 -5.51   -3.17 0   4.16 7.06   4.29 4.29   7.11 4.03   8.05 1.4   8.05 -1.4   7.11 -4.03   4.29 -4.29   4.16 -7.06   -4.16 -7.06   -4.29 -4.29				SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend
	11 12 13 14 15 16	-7.11 -4.03   -8.05 -1.4   -8.05 1.4   -7.11 4.03   -4.29 4.29   -4.16 7.06			ISS DATE Designed By:	Date:
	Н	G	F	E	TITLE SCALE NA SOURIA FORMAT A3	Alum General linear Tolerances: ± U WWW.SOURIAU. SOURIAU 8D5171

