





③ **USB2.0 COMPLIANT**



**NOTES:**

- 1.Material:
  - ① 1.1 Housing: PBT+30%GF UL94V-0, Color White
  - 1.2 Shell: SPCC
  - 1.3 Contact :Brass
- 2. FINISH:
  - 2.1 Contact Area: Selective 30u"Au
  - Solder Area: Tin Plated
  - Under: Ni Plated
- 3.MECHANICAL:
  - 3.1 Mating Force:3.57kgf Max.
  - 3.2 Unmating Force:1.02kgf Min
  - 3.3 Durability:1500 cycles Min
- 4.ELECTRICAL:
  - 4.1 Current Rating:1.5A
  - 4.2 Dielectric Strength:500V AC FOR 1 MINUTE
  - 4.3 Contact Resistance:30mΩ Max
  - 4.4 Insulation Resistance:1000 MΩ Min
- 5.Operating temperature: -55°C TO +85°C
- 6.PACKIING: Tray

**RoHS compliant**

Scale	Free				Date	Name	Customer-No.
<b>TOLERANCE</b>					Drawn	Winnie	
.X	±0.30				07.06.2013	Winnie	
.XX	±0.20	③	Update	24.07.2019	Xavier	Approved	04.04.2014
.XXX	±0.10	②	Change the Pin number	04.04.2014	Winnie		
DIM	TOL	①	Change the P/NAU-Y1008-2-R to AU-Y1008-2	25.11.2013	Winnie	Drawing-No.	
X.°	±5°	①	Drawn	07.06.2013	Winnie	<b>ASSMANN</b> WSW components	ASS 5780 CO
Angle	TOL	①	Drawn	07.06.2013	Winnie		rev03
UNIT	mm	Id.	Modification	Date	Name	Replace	SHEET

