


Support Thermocouple Type: K, J, E, T
250 Vac Isolated Input Protection

FEATURE


- Auto range.
- PC interface.
- LED back light.
- Four channel input.
- Four channel display.
- Resolution 0.1 /0.1
- With windows software.
- Auto shut off for battery saving.
- 16,000 records data logger each channel.
- Isolated input protection up to 250 Vac between any two inputs.



Four Channel Display



T1-T2 Display



SPECIFICATIONS

Measurement Range: -200°C~1372°C (K type)
-328°F~2501°F (K type)

Accuracy: -200°C~1372°C..... 0.1%rdg+0.7°C
-328°F~2501°F..... 0.1%rdg+1.4°F

Battery Type: 9V Battery

Operating Condition: -10°C to 50°C (<90%RH)

Storage Condition: -40°C to 60°C(<75%RH)

Dimensions: 197mm 65mm 36mm

Weight: Approx.310g

Accessories: Battery, Operation Manual, Carrying Case
Temperature Probe TP-K01 2Pcs
USB Cable, Software.



LED Back Light

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER[®]
CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail : center@centertek.com
FAX: 886-2-26763925 http ://www.centertek.com

Distributed by: