




UD12-9MM-9MM-SS

Ruland UD12-9MM-9MM-SS, 9mm x 9mm Double Universal Joint, Friction Bearing, Stainless Steel, 18.9mm OD, 96.9mm Length





Description

Ruland UD12-9MM-9MM-SS is a double cardan friction bearing universal joint with 9mm x 9mm bores, 18.9mm OD, and 96.9mm length. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UD12-9MM-9MM-SS is made from high grade stainless steel for increased corrosion resistance. It can be combined with boot UBOOT12/19-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT12/19-NI-KIT UPC 63452931640 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.	i roddot opoomodtiono			
Joint Outer Diameter (OD) 18.9 mm Bore Tolerance +0.025 mm / -0.000 mm Length (L) 96.9 mm Center Yoke Length (LC) 28.6 mm Yoke Length (LY) 34.1 mm Hub Depth (LH) 24.1 mm Peak Torque 89.3 Nm Rated Torque 17.9 Nm Max Operating Angle 90° Material Specification Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainles Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT12/19-NI-KIT UPC 63452931640 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application AWARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	Bore (B1)	9 mm	Small Bore (B2)	9 mm
Length (L) 96.9 mm Center Yoke Length (LC) 28.6 mm Yoke Length (LY) 34.1 mm Hub Depth (LH) 24.1 mm Peak Torque 89.3 Nm Rated Torque 17.9 Nm Max Operating Angle 90° Material Specification Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainles Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT12/19-NI-KIT UPC 63452931640 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	B1 Max Shaft Penetration	24.1 mm	B2 Max Shaft Penetration	24.1 mm
Yoke Length (LY)34.1 mmHub Depth (LH)24.1 mmPeak Torque89.3 NmRated Torque17.9 NmMax Operating Angle90°Material SpecificationYokes: 303 Stainless Steel Pins and Blocks: 416 Stainless SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT12/19-NI-KITUPC63452931640Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicationProp 65WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Care	Joint Outer Diameter (OD)	18.9 mm	Bore Tolerance	+0.025 mm / -0.000 mm
Peak Torque 89.3 Nm Rated Torque 17.9 Nm Max Operating Angle 90° Material Specification Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainles Steel Pins and Blocks: 416 Stainles Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT12/19-NI-KIT UPC 63452931640 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application of the State of Ca WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	Length (L)	96.9 mm	Center Yoke Length (LC)	28.6 mm
Max Operating Angle90°Material SpecificationYokes: 303 Stainless Steel Pins and Blocks: 416 Stainless SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT12/19-NI-KITUPC63452931640Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicationProp 65▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Cardinal Properation	Yoke Length (LY)	34.1 mm	Hub Depth (LH)	24.1 mm
Pins and Blocks: 416 Stainles Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant UPC 63452931640 Tariff Code 8483.60.4000 UNSPC Vote 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the State of Ca WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	Peak Torque	89.3 Nm	Rated Torque	17.9 Nm
Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT12/19-NI-KIT Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Nickel (metallic), known to the State of Ca	Max Operating Angle	90°	Material Specification	Pins and Blocks: 416 Stainless
UPC 63452931640 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Nickel (metallic), known to the State of Ca WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	Manufacturer	Belden Universal	Country of Origin	USA
UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	Recommended Lubricant	LUBRIPLATE No. 1200-2	Matching Boot Cover	UBOOT12/19-NI-KIT
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular applicati Prop 65 ▲ WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	UPC	63452931640	Tariff Code	8483.60.4000
Prop 65WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Ca	UNSPC	25173810		
	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State of Californ to cause cancer. For more information go to www.P65Warnings.ca.gov .		