


DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS

RoHS COMPLIANT

ASSEMBLY P/N	CONTACT QTY.		CABLE O.D. RANGE
	#16	#20	
W8C82-6PG-P-513	2	4	.1315 [3.3-3.8]
W8C82-6PG-P-516			.1618 [4.1-4.6]
W8C82-6PG-P-519			.1921 [4.8-5.3]
W8C82-6PG-P-522			.2225 [5.6-6.]
W8C82-6PG-P-526			.2527 [6.4-6.9]
W8C82-6PG-P-528			.26285 [6.6-7.2]



MAT'L: UV PBT, BLACK

WIRING END

	MA	07-20-20	RELEASED PER PDR 16014-10							
	PNK	01-18-18	PDR16014							
V.	INIT.	DATE	DESCRIPTION							
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED JUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.		ORIG. DRAWN BY: DATE: PNK 01-18-18 Checked by:			conxall					
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS. UNLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS 1:010 ANGLES 11° FRACTIONS 1:1/16		APPROVED BY:			601 E. WILDWOOD VILLA PARK, IL 60181 TITLE: CABLE-TO-CABLE ASSEMBLY 2-16 + 4-20 PIN CONTACTS, SOLDER NOT1 6 - 40-20 PIN CONTACTS, SOLDER					
		scale NTS	size B	sheet 1 OF 1	INSTA-CLICK™ MINI-CON-X POWER/SIGNAL customer: STANDARD PRODUCT					
 CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX 		FILE: W8C82-6P	G-P-5X	DIRECTORY: SLW	NUMBER: W8C82-6PG-P-5XX	REV A				