

Specification Sheet

Part Number: 157-00329

Offset mount allows wire or cable to be attached beside mounting hole instead of directly above it.

Reusable fastener can be extracted from threaded or nonthreaded holes using a 5/16" hex driver.

Delivers high extraction force for reliable performance, yet it's easy to install.

Heat stabilized material provides excellent resistance to high temperatures.



Blind Hole Mount Cable Tie, Offset, 8"L, .25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bag

Article Number	157-00329
Type	T50ROSBHMBSO18
Color	Black (BK)
Quantity Per	bag

Product Description Blind Hole Mount Offset Cable Ties secure bundles beside the mounting hole instead of directly above it. The unique design includes a heat stabilized cable tie and formula-matched, hex-head fastener that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or non-threaded blind holes. Since cable or wire bundle is beside the fastener, the assembly can be removed using a hex driver from the mounting hole without cutting the cable tie. The fastener can then be reused.

Short Description Blind Hole Mount Cable Tie, Offset, 8"L, .25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bag

Global Part Name T50ROSBHMBSO18-PA66HS-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225.0

Length L (Imperial) 8.0

Length L (Metric) 203.2

Offset Length (Imperial) 0.71

Offset Length (Metric) 18.0

Fixation Method Blind Plug

Identification Plate Position none

Releasable Closure No

Width W (Imperial) 0.185

Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.736
Height H (Metric)	18.7
Diameter D (Imperial)	0.25
Diameter D (Metric)	6.35
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.35 mm
Mounting Hole Diameter D Min (Imperial)	0.246
Mounting Hole Diameter D Max (Imperial)	0.254
Mounting Hole Diameter D Max (Metric)	6.45

Material

Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut	PA66HS
Flammability	UL 94 V-2
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500