



3 Type

D With tapped through bore  
E With tapped blind bore

Inch table

1 2

Dimensions in: inches - millimeters

d <sub>1</sub>	d <sub>3</sub> Thread Type E		d <sub>4</sub>	h	k	t <sub>1</sub> min.
0.79 20	8 x 32	10 x 32	0.45 11.5	0.63 16	0.39 10	0.24 6
1.02 26	10 x 32	1/4 x 20	0.63 16	0.75 19	0.43 11	0.31 8
1.26 32	1/4 x 20	5/16 x 18	0.67 17	0.87 22	0.51 13	0.39 10

Metric table

1 2 3

Dimensions in: millimeters - inches

d <sub>1</sub>	d <sub>2</sub> Thread Type D			d <sub>3</sub> Thread Type E			d <sub>4</sub>	h	k	t <sub>1</sub> min.	t <sub>2</sub>		
	Type D	Type D (ESD)	Type E	Type E (ESD)	Type E	Type E (ESD)							
12 0.47	-	-	-	-	M 3	M 4	M 5	-	9.5 0.37	11.5 0.45	7.5 0.30	6 0.24	-
16 0.63	M 4	M 5	-	M 5	M 3	M 4	M 5	M 4	11 0.43	13 0.51	8 0.31	6 0.24	10 0.39
20 0.79	M 6	-	-	M 6	M 5	M 6	-	M 5	11.5 0.45	16 0.63	10 0.39	6 0.24	12 0.47
25 0.98	M 6	M 8	-	M 8	M 5	M 6	-	M 6	16 0.63	19 0.75	11 0.43	6 0.24	14 0.55
32 1.26	M 6	M 8	M 10	M 10	M 8	-	-	M 8	17 0.67	22 0.87	13 0.51	10 0.39	16 0.63
40 1.57	M 10	-	-	-	M 8	M 10	-	-	19 0.75	27 1.06	14 0.55	13 0.51	20 0.79
50 1.97	M 10	-	-	-	M 10	-	-	-	22 0.87	28.5 1.12	15 0.59	13 0.51	20 0.79

Specification

- Body  
Plastic  
Technopolymer (Polyamide PA) —  
- Reinforced  
- Temperature resistant up to 266 °F (130 °C)  
- Black, matte finish
- Body  
Plastic  
Technopolymer (Polyamide PA)  
Electrically conductive (antistatic) **ESD**
- Tapped insert  
Brass
- RoHS compliant

Information

EN 590 knurled nuts, type ESD are made from a conductive plastic material which prevents electrostatic loading. The imprint "ESD" defines the special antistatic properties according to IEC 61340-5-1.

How to order (Inch)

1	Handle diameter d <sub>1</sub>
2	Thread d <sub>3</sub>
3	Type

**EN 590-26-1/4X20-E**

How to order (Metric, ESD plastic)

1	Handle diameter d <sub>1</sub>
2	Thread d <sub>2</sub> (Thread d <sub>3</sub> )
3	Type
4	Material

**EN 590-32-M10-D-ESD**

1.1  
1.2  
1.3  
1.4  
1.5  
2.1  
2.2  
2.3  
2.4