т 	Q	г		m		0	₩	A	
	Z	ØS							
22			Jan Start St			LAYOUT SHOWN AS EXA	AMPLE		
		Keying Sho	own as example						
CHARACTERISTICS		, ,		star dimension					
-Standard : Based on MIL-I)TL-38999 Series III		Dim	ector dimension Nominal					
-Shell Material : A	Aluminium		ØS Z	25 Max 31 Max		SOURIAU shall not be liable for any	non-conformity or dam	age	
	Black Zinc Nickel		VV THREAD			due to a use of the Products whic	ch does not comply with	ו	
	hermoplastic					the Specifications issued by either of t (professional recommendation)		party	
	Copper Alloy								
	ilicon Elastomer					Country			
_	Gold over copper Alloy 0.8μm minim	um				FR	Not Lis	leu	
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories					PN: 8D511Z22PN			
						1			
	-65°C to +175°C 500 hours				A 18-10-2016	First Release			
	.4.47 g ± 10%				ISS DATE	Latest modification - by		MOL	D N°
	J				Designed By:	Date:	CUSTO	MER DRAWING	
					TITLE	Alumini	um Plug 8D serie	25	
BASIC SERIES:	8D 5 - 11	Z 22 P N	I		SCALE	General linear	NPR	DS / PROJECT	
					NA	Tolerances:		859	
SHELL TYPE : Plug with RF								s document is the property of	
CONTACT TYPE : Standa	d Crimp Contact			ORIENTATION : N	SOURIAU	WWW.SOURIAU.CO	DM it	SOURIAU must not be reproduced or	
SHELL SIZE : 11				CONTACT TYPE : PIN(500 Matings)			com	municated without permission	
PLATING : Z = Blac	k Zinc Nickel			CONTACT LAYOUT : 11-22	FORMAT A3	SOURIAU		SHE	ET
					1 1 1	8D511Z2			/2

	Т	۵	п п	m	D	0	
		Contact Layout					
4							
	Ctc A B	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905					
ယ	C D	-1.905 -1.905 -1.905 1.905					
	-					SOURIAU shall not be liable due to a use of the Proc the Specifications issued by o (professional recom	ducts w either (
0						PN: 8D	Count FR
					A 18-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:	
					SCALE	A General	lumi
<u> </u>							inces:
					FORMAT	SOUF	

G

Н

F

Е

A3

D

С



 \triangleright

σ