# PRODUCT DATASHEET CP17572\_YASMEEN-70-S-C-WHT

### YASMEEN-70-S-C-WHT

~15° spot beam. Assembly with holder C compatible with LEDiL HEKLA. White version.

#### **SPECIFICATION:**

Dimensions	Ø 69.9 mm
Height	39.9 mm
ROHS compliant	yes 🛈



#### **MATERIALS:**


Component	Туре	Material	Colour	Finish
YASMEEN-70-S	Single lens	PMMA	clear	
YASMEEN-70-HLD-C-WHT	Holder	PC	white	

#### **ORDERING INFORMATION:**

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP17572_YASMEEN-70-S-C-WHT	Single lens	105	105	15	9.8
» Box size: 476 x 273 x 305 mm					




# PRODUCT DATASHEET CP17572\_YASMEEN-70-S-C-WHT



See also our general installation guide: www.ledil.com/installation\_guide





# PRODUCT DATASHEET CP17572\_YASMEEN-70-S-C-WHT

# **OPTICAL RESULTS (MEASURED):**




LED Vesta DTW 15mm (33W)

FWHM / FWTM 23.0° / 39.0° Efficiency 92 % Peak intensity 4.9 cd/lm LEDs/each optic 1

Light colour Tunable White

Required components:

Bender Wirth: 632b Hekla XL




#### bridgelux.

LED Vesta DTW 9mm (4W/6W/12W)

FWHM / FWTM 15.0° / 25.0°
Efficiency 93 %
Peak intensity 11 cd/lm
LEDs/each optic 1

Light colour Tunable White


Required components: Bender Wirth: 652b Hekla



# **CITIZEN**

LED CLL02x/CLU02x (LES10)

FWHM / FWTM 15.5° / 26.5°
Efficiency 92 %
Peak intensity 10 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17435\_HEKLA-G2-C




# **CITIZEN**

 LED
 CLL03x/CLU03x


 FWHM / FWTM
 21.0° / 37.0°


 Efficiency
 92 %

Peak intensity 5.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17438\_HEKLA-G2-I










# PRODUCT DATASHEET CP17572\_YASMEEN-70-S-C-WHT

### **OPTICAL RESULTS (MEASURED):**

# **SAMSUNG**

LED LC016D / LC019D / LC026D / LC033D

FWHM / FWTM 23.0° / 40.0°
Efficiency 92 %
Peak intensity 4.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:





# **SAMSUNG**

F17438\_HEKLA-G2-I

LED LC030C/040C G2
FWHM / FWTM 17.0° / 30.0°
Efficiency 92 %

Peak intensity 7.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17438\_HEKLA-G2-I






# SEOUL SEMICONDUCTOR

LED MJT COB LES 14.5

FWHM / FWTM 23.0° / 39.0°
Efficiency 92 %
Peak intensity 4.9 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17438\_HEKLA-G2-I





# **TRIDONIC**

 LED
 SLE G7 LES09


 FWHM / FWTM
 15.0° / 25.0°

 Efficiency
 93 %

 Peak intensity
 11.3 cd/lm

LEDs/each optic 1
Light colour White
Required components:
F17435\_HEKLA-G2-C





# TRIDONIC LED SLE G7 LES15 FWHM / FWTM 22.0° / 38.0° Efficiency 92 % Peak intensity 5.1 cd/lm LEDs/each optic 1 Light colour White Required components: F17438\_HEKLA-G2-I

Published: 21/10/2020




## **OPTICAL RESULTS (SIMULATED):**

# **CITIZEN**

LED CLU712/713
FWHM / FWTM 14.0° / 26.0°
Efficiency 93 %
Peak intensity 11.3 cd/lm
LEDs/each optic 1
Light colour White

Required components: F17438\_HEKLA-G2-I



Published: 21/10/2020



# PRODUCT DATASHEET CP17572\_YASMEEN-70-S-C-WHT

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

10/10

www.ledil.com/ where\_to\_buy