

## LDEID2820MA0N00

Aliases (DEID2820MA0N00)

LDE, Film, Metallized PEN Stacked, Automotive Grade, 0.082 uF, 20%, 120 VAC, 250 VDC, 125°C, 2220, 3.5mm



Click [here](#) for the 3D model.

### Dimensions

|           |                   |
|-----------|-------------------|
| Chip Size | 2220              |
| L         | 6mm +/-0.3mm      |
| W         | 5mm +/-0.4mm      |
| T         | 3.5mm MAX         |
| B         | 0.4mm +0.5/-0.3mm |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | T&R  |
| Packaging Quantity | 2250 |

### General Information

|                |                        |
|----------------|------------------------|
| Series         | LDE                    |
| Dielectric     | Metallized PEN Stacked |
| Style          | SMD Chip               |
| Features       | Automotive Grade       |
| RoHS           | Yes                    |
| Qualifications | AEC-Q200               |
| AEC-Q200       | Yes                    |
| Shelf Life     | 104 Weeks              |
| MSL            | 2a                     |

### Specifications

|                       |            |
|-----------------------|------------|
| Capacitance           | 0.082 uF   |
| Capacitance Tolerance | 20%        |
| Voltage AC            | 120 VAC    |
| Voltage DC            | 250 VDC    |
| Temperature Range     | -55/+125°C |
| Rated Temperature     | 125°C      |
| Dissipation Factor    | 0.8% 1kHz  |
| Insulation Resistance | 1 GOhms    |
| Max dV/dt             | 100 V/us   |