

R73UI1180SE00J

Aliases (73UI1180SE00J)

R73, Film, Film/Foil Polypropylene, Automotive Grade, 1800 pF, 5%, 2000 VDC, 85°C, Lead Spacing = 15mm



Click here for the 3D model.

Dimensions	,
L	18mm +/-0.5mm
Н	13.5mm +0.1/-0.5mm
Т	7.5mm +0.2/-0.5mm
S	15mm +/-0.4mm
LL	4mm +2mm
F	0.8mm +/-0.05mm

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	1000	

General Information		
Series	R73	
Dielectric	Film/Foil Polypropylene	
Style	Radial	
Features	Automotive Grade, Pulse	
RoHS	Yes	
Lead	Cut	
Qualifications	AEC-Q200	
AEC-Q200	Yes	
Component Weight	2.3 g	
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

Specifications		
Capacitance	1800 pF	
Capacitance Tolerance	5%	
Voltage AC	500 VAC	
Voltage DC	2000 VDC	
Temperature Range	-55/+105°C	
Rated Temperature	85°C	
Dissipation Factor	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz	
Insulation Resistance	100 GOhms	
Max dV/dt	54000 V/us	
Inductance	10 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.