

Specification Sheet


Part Number: 596-00792

Made with UV stable inks and materials for durability and weather resistance.

Supplied with aggresive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers.



Peel-Off Paint Shield, UV Stable, 3.6" x 2.38", PET, Clear, 10/pkg

Article Number 596-00792

Type PAINTSHIELD1

Color Clear (CL)

Quantity Per pack

Product Description HellermannTyton offers Paint Shield laminates that can be applied

over Metal Solar Placards as a barrier against unintentional painting or graffiti. Paint Shields can also be used to provide additional protection for hand-written markings using a paint pen.

HellermannTyton offers several sizes of Paint Shields designed to match all sizes of Metal Solar Placards. If a Paint Shield (covering placard) has been painted over, simply remove the shield to reveal

original marking. Replace shield as needed.

Short Description Peel-Off Paint Shield, UV Stable, 3.6" x 2.38", PET, Clear, 10/pkg

Global Part Name PAINTSHIELD1-240-CL

Technical Description 3.6" X 2.375" for use with 596-00829, 596-00496

Width W (Imperial) 3.6

Width W (Metric) 91.44

Thickness T (Metric) 64.0

Height H (Imperial) 2.375

Height H (Metric) 60.42

Material Type 240, 2.0 Mil Polyester, Clear (240)

Material Shortcut 240

Adhesive 1.0 Mil Aggressive Removable

Halogen Free No

Adhesive Operating Temperature from +50°F (from +10°C)

Operating Temperature -20°F to +302°F (-29°C to +150°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Warranty (US)	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919905060
Labels per Column	1
Labels per Row	1

© 2021 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions