# Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions

$$\label{eq:max-ey} \begin{split} \text{Max-Eyth-Straße 1} & \cdot 74638 \ \text{Waldenburg} \cdot \text{Germany} \\ \text{Tel.} & +49 \ (0) \ 79 \ 42 \ 945 - 400 \\ \text{eiSos@we-online.de} & \cdot \ \text{www.we-online.de} \end{split}$$



Product / Process Change Notification (PCN)  ☐ Major change ☐ Minor change					
PCN #:	PCN_ConCON_20200701	Change Category:			
Affected Series:	WR-USB3; 692221030100	<ul><li>□ Equipment / Location</li><li>□ General Data</li><li>□ Material</li></ul>			
PCN Date:	June 01, 2020	□ Process			
Effective Date:	July 01, 2020	<ul> <li>□ Product Design</li> <li>☑ Shipping / Packaging</li> <li>□ Supplier</li> <li>□ Software</li> </ul>			
Contact:	Product Management	Data Sheet Change:			
Phone:	+49 (0) 7942 - 945 5001	⊠ Yes □ No			
Fax:	+49 (0) 7942 - 945 5179	Attachment:			
E-Mail:	pcn.eican@we-online.com	□ Yes ⊠ No			

# **DESCRIPTION AND PURPOSE OF CHANGE:**

In order to enhance the product reliability, Würth Elektronik will change the trays used for this reference.

All products with date code 2020-05-05 or later, will be affected by this change.

There will be no change in form, fit, function, quality or reliability of the product.

### **DETAIL OF CHANGE:**

The Package will be changed as below:

# BEFORE CHANGE Top cover: Top cover: Carton Dimension: 355 x 355 x 330 mm Top cover: Carton Dimension: 350 x 280 x 320 mm

# Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions

$$\label{eq:max-ey} \begin{split} \text{Max-Eyth-Straße 1} & \cdot \text{74638 Waldenburg} \cdot \text{Germany} \\ \text{Tel.} & \cdot \text{449 (0) 79 42 945-0} \cdot \text{Fax } \cdot \text{449 (0) 79 42 945-400} \\ \text{eiSos@we-online.de} & \cdot \text{www.we-online.de} \end{split}$$



There is no change of packaged quantity per tray or per carton.

Part number	BEFORE CHANGE		AFTER CHANGE	
	SPQ Tray	CPQ Carton	SPQ Tray	CPQ Carton
692221030100	50	1600	50	1600

# **RELIABILITY / QUALIFICATION SUMMARY:**

Product approval is according to specification and is internally released by the Product Management Department