 	т п		0	₿ >		
			LAYOUT SHOWN AS EXAM	MPLE		
	Keying Shown as example					
CHARACTERISTICS						
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material       : Aluminium         -Shell Plating       : Nickel         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy	Z     31 Max       VV THREAD     M25x1-6g			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8μm minimum			FR	Not Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D517F08BE			
-Temperature Range : -65°C to +200°C		A 14-10-2016	First Release			
-Salt Spray : 48 hours						
Mass : 37.62 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 17 F 0	8 B E	SCALE	General linear	NPRDS / PROJECT		
BASIC SERIES: 8D 5 - 17 F 0 SHELL TYPE : Plug with RFI Shielding		NA -	Tolerances:	859		
	ORIEN			This document is the pr	operty of	
CONTACT TYPE       : Standard Crimp Contact         SHELL SIZE : 17       CONTACT TYPE : SOCKET(500 Matings)						
PLATING : F = Nickel	CONTACT HTE . SOCKET(SOC				SHEET	
	CONTACT LATO	A3	8D517F08		1/2	
					1/2	

_	Ŧ	۵	г п	m	U	0
		Contact Layout				
4	-x (	$ \begin{array}{c}                                     $				
	Contribution of the second sec	Contacts           (Insert arrangement 17-8)           act           X-axis           (mm)           (mm)           + 0.00 (0.00)         + 2.36 (5.99)           + 1.28 (3.25)         + 0.06 (2.18)           + 2.30 (5.84)         - 0.78 (1.98)           + 0.94 (2.39)         - 216 (5.49)				
ω	G H Shell Arrangement Nu	128 (3.25) +.086 (2.18)				
						SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either o
N						(professional recommenda Count FR PN: 8D517
_					A 14-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
<u> </u>					SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	WWW.SOURIAU. SOURIAU 8D517F
L	Н	G	F	E	D	C

