

ARCA 406021 No MP



Sample image

Order symbol: ARCA 406021 No MP

Product nbr: 8120026N

Description: Cabinet. PC


Remarks: Grey cover. 2-point locking. hinges on the short side

EAN: 6418074089441

El. number:

- Finland:
- Denmark:
- Sweden:

Including: Cabinet base. door with PUR gasket. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.



Dimensions:	Height	Width	Depth
mm:	400	600	210
inch:	15.75	23.62	8.58

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey

Accessories:

MPS ARCA 6040	Mounting plate (550x350x2 mm) (550 x 350 x 2)
PMK ARCA 60	PoleMounting kit. for pole \varnothing 100-300mm (585 x 385 x 35)
MPP ARCA 4060	Mounting plate perforated (550x350x2 mm - 26x11 mm) (350 x 550 x 2)
DSP ARCA HRS	Door stopper ARCA. horizontal. right. small

Cover colour: RAL 7035 -light grey
Gasket material: Polyurethane

Temperatures:

Temperature °C (short term):: -40 ... 120
Temperature °C (continuous): -40 ... 80
Temperature °F (short term): -40 ... 250
Temperature °F (continuous): -40 ... 175

IDS ARCA 4060	Inner door set (385 x 585 x 35)
DSP ARCA HLS	Door stopper ARCA. horizontal. left. small
SBK ARCA 40	Support bar kit (340 x 40 x 30)
MPMP ARCA 6040	Mounting plate multiperforated (550x350x2 mm - ø3.6 mm) (550 x 450 x 2)
DRS ARCA 406021	DIN rail frame set (585 x 385 x 35)
MPX ARCA 6040	Mounting plate (550x350 mm) (550 x 350 x 5)
SBK ARCA 60	Support bar kit (535 x 40 x 30)
RCS ARCA 4060	Rain canopy set for size 4060 (20 x 600 x 30)

Rating:

Ingress protection (EN 60529):	IP66;
Impact Resistance (EN 62262):	IK10;
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C:	960 °C
NEMA Class	NEMA 1, 4, 4X, 12 and 13

Certificates:

Certificate FI 40467