

## External 240V Battery Pack for Select Tripp Lite 400V 3-Phase SmartOnline UPS Systems

MODEL NUMBER: **BP240V135**



240V DC battery extends the runtime of select Tripp Lite 400V 3-phase SmartOnline® UPS systems.

### Description

The BP240V135 External Battery Pack extends the runtime of compatible Tripp Lite SmartOnline UPS systems recommending its use, including SVT10KX, SVT20KX and SVT30KX. It comes with heavy-gauge cabling and a high-current DC connector for safe, simple hardwired installation, as well as internal disconnect for battery isolation. A built-in circuit breaker protects your equipment from dangerous overcurrent or overloads. For even more battery runtime, you can daisy-chain multiple BP240V135 battery packs to the compatible UPS system. Tested to IEC 62040-1: 2008/A1: 2013 standards.

### Features

#### Extends Runtime of Select SmartOnline UPS Systems

- Connects to Tripp Lite's SVT10KX, SVT20KX, SVT30KX and other 3-phase UPS systems recommending its use
- Includes cable with high-current DC connector
- Internal DC disconnect for battery isolation
- Built-in circuit breaker
- Can be daisy-chained with multiple battery packs for extended-run operation
- Tested to IEC 62040-1: 2008/A1: 2013 standards

### Highlights

- Includes cable with high-current DC connector
- Internal DC disconnect for battery isolation
- Built-in circuit breaker
- Daisy-chainable with multiple batteries for longer operation
- Tested to IEC 62040-1: 2008/A1: 2013 standards

### Package Includes

- BP240V135 External Battery Pack
- Battery connection cable
- Owner's manual

## Specifications

OVERVIEW	
UPC Code	037332196569



<b>INPUT</b>	
Input Phase	3-Phase
<b>BATTERY</b>	
Expandable Battery Runtime	Multiple BP240V135 battery packs can be daisy-chained to the UPS for extended runtime
DC System Voltage (VDC)	240VDC
UPS Connection	DC connector
<b>PHYSICAL</b>	
External Battery Pack Form Factor	Tower
Material of Construction	Steel
Shipping Dimensions (hwd / cm)	66.04 x 37.01 x 100.00
Shipping Dimensions (hwd / in.)	26.00 x 14.57 x 39.37
Shipping Weight (kg)	211.37
Shipping Weight (lbs.)	466.00
Unit Dimensions (Height x Width x Depth, mm)	580 x 250 x 826
Unit Dimensions (hwd / cm)	58 x 25 x 82.6
Unit Dimensions (hwd / in.)	22.84 x 9.85 x 32.5
Unit Weight (kg)	155.13
Unit Weight (lbs.)	342
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>