

**LL TTB 6/1 BL****Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

**Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

**General ordering data**

Order No.	<a href="#">2710240000</a>
Type	LL TTB 6/1 BL
GTIN (EAN)	4050118847918
Qty.	50 pc(s).

## LL TTB 6/1 BL

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)

## Technical data

[www.weidmueller.com](http://www.weidmueller.com)

0.157 inch

0.776 inch

0.299 inch

### Temperatures

-25 °C...55 °C

Continuous operating temp., min. -60 °C

Continuous operating temp., max. 130 °C

### Material data

Material Wemid

Colour blue

UL 94 flammability rating V-0

### Classifications

ETIM 6.0 EC002848

ETIM 7.0 EC002848

ETIM 8.0 EC002848

ECLASS 9.0 27-14-11-92

ECLASS 9.1 27-14-11-92

ECLASS 10.0 27-14-11-92

ECLASS 11.0 27-14-11-92

ECLASS 12.0 27-14-11-92

### Downloads

Engineering Data [CAD data – STEP](#)Engineering Data [EPLAN](#)Catalogues [in PDF-format](#)

Depth	4 mm	Depth (inches)	0.157 inch
Height	19.7 mm	Height (inches)	0.776 inch
Width	7.6 mm	Width (inches)	0.299 inch
Net weight	0.39 g		

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-60 °C
Continuous operating temp., max.	130 °C		

Material	Wemid	Colour	blue
UL 94 flammability rating	V-0		

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ETIM 8.0	EC002848	ECLASS 9.0	27-14-11-92
ECLASS 9.1	27-14-11-92	ECLASS 10.0	27-14-11-92
ECLASS 11.0	27-14-11-92	ECLASS 12.0	27-14-11-92

Engineering Data	<a href="#">CAD data – STEP</a>
Engineering Data	<a href="#">EPLAN</a>
Catalogues	<a href="#">in PDF-format</a>