

- INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0 CONTACT MATERIAL; COPPER, NICKEL, TIN ALLOY CA-725
- CONTACT PLATING: GOLD ON THE MATING AREA, TIN-LEAD ON THE CONTACT TAILS, NICKEL UNDERPLATE

\*FOR ALL OTHER SPECIFICATIONS REFER TO SHEET 4\*


### 346/396 SERIES CARD EDGE CONNECTOR PART NUMBER: 346-094-500-201

YOUR CONNECTION TO QUALITY & SERVICE

	ACAD REFERENCE NO	. 346-ENG-MASTER			
	DRAWN: J.LEE	DATE: APR. 22/09			
	CHECKED:	DATE:			
	SCALE: 1:1	SHEET 1 OF 3			
0	DRAWING NUMBER	ISSUE			

346-ENG-MASTER





.060 [1.52] .200 [5.08] .210 [5.33] .660 [16.76]

.060 [1.52] .150 [3.81] .260 [6.6] -Outside Tails .660 [16.76] **Outside Tails** 

.165 [4.19] .375 [9.54] .125(3.18) to .210(5.33) .125(3.18) to .210(5.33)

**Contact Code 558** 

#### **Contact Code 559**

**Contact Code 560** 

- INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0 CONTACT MATERIAL; COPPER, NICKEL, TIN ALLOY CA-725
- CONTACT PLATING: GOLD ON THE MATING AREA, TIN-LEAD ON THE CONTACT TAILS, NICKEL UNDERPLATE

\*FOR ALL OTHER SPECIFICATIONS REFER TO SHEET 3\*

## 346/396 SERIES CARD EDGE CONNECTOR CONTACT CODE 555,556,558,559,560 DIMENSIONS



346-ENG-MASTER DATE: APR. 22/09 J.LEE 1:1 SHEET 2 OF 3

346-ENG-MASTER

ISSUE NUMBE

ORIGINAL



#### **Features**

- CSA Approved and UL Recognized
- .125 (3.18) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- High Profile Insulator Body, .600 (15.24)
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree & Degree &
- Single or Dual Row Configurations
- Large Variety of Mounting Options, Flush or Offset Lugs
- Pre-assembled Card Guides Available
- Accepts Between Contact and In-Contact Polarizing Keys
- Automatic Wire Wrap Positioning Holes

# **Specifications**

- Insulator Material: Thermoplastic Polyester, UL 94V-0
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 3 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1500 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Résistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +125 Degrees C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

346/396 SERIES CARD EDGE CONNECTOR			ACAD REFERENCE NO. 346-ENG-MASTER			
FEATURES AND SPECIFICATIONS		DRAWN:	J.LEE	DATE: A	PR. 22/09	
		CHECKED:		DATE:		
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS	SCALE:	1:1	SHEET ;	3 OF 3	
I   SII   III	ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING	NUMBER	•	ISSUE	
		346	5-ENG-MASTER		1	