


THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.






N	0	Т	E	S	1

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)
SIGNAL CONTACT CURRENT RATING:	
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC	•
WITHSTANDING VOLTAGE:	1000V AC rms

				SW REFERENCE NO.: 630 COMBO ASSEMBLY				
COMBINATION	DRAWN: C.B	DATE: JAN. 01/2019						
			DATE:					
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2				
TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-11W	1250-1T5	ISSUE				
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-11W	1250-1T5	1				



ĦS

COMPLIANT

Г

