


THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.






10.70


5.80

| Ν | 0 | TΕ | S: |
|---|---|----|----|
| | | | |

| MATERIAL: HOUSING: SHELL: CONTACT: | THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED |
|--|--|
| OPERATING TEMPERATURE: | -55°C ~ 125°C |
| POWER/CO-AX CONTACT RATING: (IF PRESENT) | 30A (CURRENT) |
| SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE: | 5A PER CONTACT 10mΩ MAX. |
| INSULATOR RESISTANCE: DIELECTRIC | 5000MΩ min. |
| WITHSTANDING VOLTAGE: | 1000V AC rms |



| | | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | | |
|--------------------|--------------------------------------|--|--------------------------------------|--------------------|-------|--|
| | | | DRAWN: C.B | DATE: JAN. 01/2019 | | |
| | | | CHECKED: | DATE: | | |
| YOUR CONNECTION TO | EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| | TORONTO, ONTARIO CANADA | | DRAWING NUMBER: 630-2WK | 2650-3TB | ISSUE | |
| | YOUR CONNECTION TO QUALITY & SERVICE | | PART NUMBER: 630-2WK | 2650-3TB | 1 | |



HS

COMPLIANT

П

