	m m		0	B		
Z Prealult Pre						
			LAYOUT SHOWN AS EXAM	MPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	: Nickel VV THREAD M18x1-6g			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	Not Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D513F26BC			
-Temperature Range : -65°C to +200°C		A 17-10-2016	First Polosso			
-Salt Spray : 48 hours						
Mass : 27.44 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 13 F 2	26 B C	SCALE	General linear	NPRDS / PROJECT		
BASIC SERIES: 8D 5 - 13 F 2 SHELL TYPE : Plug with RFI Shielding	26 B C	NA	Tolerances:	859		
CONTACT TYPE : Standard Crimp Contact	ORIENTATIO			This document is the pro	operty of	
SHELL SIZE : 13	CONTACT TYPE : SOCKET(500 Mat					
PLATING : F = Nickel	CONTACT TIPE : SOCKET(SOUMAL	—	SOURIAU D	communicated without p	SHEET	
	CONTACT LATOUT . I		8D513F26			
		/\J	XIISIZE/6		1/2	

_	Ŧ	G	г П	m	D	0
		Contact Layout				
4		26				
		2#12 6#22D				
ω	Ctc A B C D E F 1 2	13-26 X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 4.34 3.25 0 -3.25 0				
	_					
N						SOURIAU shall not be liable for and due to a use of the Products wh the Specifications issued by either of (professional recommendat Countr FR PN: 8D513I
					A 17-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					SCALE	General linear Tolerances:
					SOURIA	J WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513F2
L	Н	G	F	E	D	C

