

C0805Q561F5GAL7189

GR900 SMD Space, Ceramic, 560 pF, 1%, 50 VDC, BP, N/A, 0805



Click here for the 3D model.

Dimensions			
Chip Size	0805		
L	2.03mm +/-0.38mm (0.08 in +/-0.015 in)		
W	1.27mm +/-0.38mm (0.05 in +/-0.015 in)		
Т	1.4mm MAX (0.055 in MAX)		
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)		

Packaging Specifications				ns
_				

Packaging T&R, Plastic Tape

General Information	
Series	GR900 SMD Space
Style	SMD Chip
RoHS	No
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
SCIP Number	1ad5a336-6d42-4be4-8c77-6a49b97cd931
Termination	Lead (SnPb)
Failure Rate	N/A
Testing and Reliability	Mil-PRF-123 Group A
Qualifications	MIL-PRF-123 Group A
AEC-Q200	No
Shelf Life	78 Weeks
MSL	1

Specifications					
Capacitance	560 pF				
Capacitance Tolerance	1%				
Voltage DC	50 VDC				
Temperature Range	-55/+125°C				
Temperature Coefficient	BP				

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.