


## C326C225J5N5TA91707301

GoldMax 300 Auto X8L HT150C, Ceramic, 2.2 uF, 5%, 50 VDC, X8L, "GoldMax, Automotive Grade", Lead Spacing = 2.54mm



Click here for the 3D model.

Dimensions	
L	5.08mm MAX
Н	7.62mm MAX
Т	3.18mm MAX
S	2.54mm +/-0.78mm
НО	16mm +/-0.5mm
F	0.51mm +0.1/-0.025mm
E	5.08mm NOM

Packaging Specifications	
Packaging	T&R, 305mm
Packaging Quantity	2500

General Information			
Series	GoldMax 300 Auto X8L HT150C		
Style	Radial		
Description	"GoldMax, Automotive Grade"		
Features	Automotive Grade		
RoHS	Yes		
Termination	Tin		
Failure Rate	N/A		
Qualifications	AEC-Q200		
AEC-Q200	Yes		
Halogen Free	Yes		

Specifications				
Capacitance	2.2 uF			
Capacitance Tolerance	5%			
Voltage DC	50 VDC			
Dielectric Withstanding Voltage	125 VDC			
Temperature Range	-55/+150°C			
Temperature Coefficient	X8L			
Dissipation Factor	2.5%			
Aging Rate	3% Loss/Decade Hour			
Insulation Resistance	454.5 MOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.