


NO.	MASSE / DIMENSION
A	2-18NS-2A
B	32.5
C	1 3/4-18NS-2A
D	11
E	22.2
F	4
G	62
H	44.5
I	57
K	4.4

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICHTKÖRPER / GROMMET
4	ENDRING / ENDRING
5	KONTAKTSTIFT/ CONTACT PIN
8	DOSENGEHÄUSE / SHELL
14	F-ENDGEHÄUSE / F-ENDBELL



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER

description **CA3100F32-8P-F80**
 Wall mounting receptacle
 Endbell for flex tube
 AWG Crimp / Pin / Layout: 32-8

ITT
 Engineered for life
 ITT CANNON GmbH
 D - 71384 Weinstadt/Germany

© All rights reserved. Reproduction or issue to third in any form
 whatever is only permitted with written authorization of ITT Cannon

page 1/1
 revision 929 11. Jun 19