

# Computer Cable, AT Serial Gold Adapter DB9M to DB25F

# MODEL NUMBER: P104-000



### Description

Tripp Lite's serial adapter has gold plated connectors and will connect a serial device with a DB25 connection to a DB9 cable or port. Gold plated copper contacts provide maximum conductivity and keep data loss to a minimum. 28 AWG stranded tinned copper conductors are individually insulated in polypropylene. This minimizes cross talk and ensures high-speed, error-free transmission. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

### Features

- Connects a DB25 serial device to a DB9 cable or port
- · Gold plated contacts and connectors for superior conductivity
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

# **Specifications**

OVERVIEW		
UPC Code	037332011664	
PHYSICAL		
Shipping Dimensions (hwd / cm)	17.14 x 10.16 x 1.27	
Shipping Dimensions (hwd / in.)	6.75 x 4.00 x 0.50	
Shipping Weight (kg)	0.05	
Shipping Weight (lbs.)	0.11	
CONNECTIONS		

## Highlights

- Converts a DB25 male serial port into a DB9 male port
- Fully shielded against EMI/RFI interference

### **System Requirements**

• DB25M serial port on a PC

#### **Package Includes**

 Serial adapter block DB9M to DB25F gold connectors



Side A - Connector 1	DB9 (MALE)	
Side B - Connector 1	DB25 (FEMALE)	
FEATURES & SPECIFICATIONS		
Technology	DB25; Serial (RS232)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies