



S1	
1	SILVER
2	RED
3	BLACK
4	WHITE
5	BLUE

WIRING DIAGRAM

- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PACKAGING: PART IS PACKED UNASSEMBLED IN POLY BAG ALONG WITH INSTRUCTION SHEET
 4. LABELING: BARCODE LABEL IS ATTACHED TO OUTSIDE OF POLY BAG
 5. MATES WITH: 5/C MALE RECEPTACLE
 6. ELECTRICAL SPECIFICATIONS:
VOLTAGE RATING: 600V AC/DC
CURRENT RATING: 8 AMPS

7	1	O-RING	NITRILE	BLACK
6	1	COMPRESSION NUT	POLYAMIDE PAG	BLACK
5	1	GROMMET	NEOPRENE	BLACK
4	5	CONTACT SOCKET	Cu ALLOY	GOLD PLATED
3	1	COUPLER	BRASS	NICKEL PLATED
2	1	SOCKET INSERT	POLYURETHANE	BLACK
1	1	CONNECTOR BODY	POLYAMIDE PAG	BLACK
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

RELEASED
 EC NO: WNA2010-0417
 DR: W. STONE 2010/01/21
 CHK: B. WOODMAN 2010/01/22
 APPR: J. MURPHY 2010/01/25

QUALITY SYMBOLS
 ▽=0
 ▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm INCH
4 PLACES	±.005 ±.0005
3 PLACES	±.005 ±.0005
2 PLACES	±.005 ±.0005
1 PLACE	±.005 ±.0005
ANGULAR ±1/2°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
IN/MM	
DRAWN BY	DATE
R. STONE	2010/01/13
CHECKED BY	DATE
B. WOODMAN	2010/01/15
APPROVED BY	DATE
J. MURPHY	2010/01/22
MATERIAL NO.	
848569101	

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
1:1	INCH	☉
TITLE		
MINI CHANGE CONNECTOR FIELD ATTACHABLE 5/C, FEMALE		
MOLEX INCORPORATED		
DOCUMENT NO.	SHEET NO.	
SD-84856-010	1 OF 1	
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		