



.XX ±0.13 .XXX ±0.05

ISSUE NUMBER	
ORIGINAL	(1)





## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

**OPERATING TEMPERATURE:** 

40A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX. INSULATOR RESISTANCE: 5000MΩ min.


DIELECTRIC WITHSTANDING VOLTAGE:



	COMBINATION D-SUB			SW REFERENCE NO.: 629 COMBO ASSEMBLY			
				DRAWN:	C.B	DATE: JAN. 01/20	19
				CHECKED:		DATE:	
			THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (	(IN C.A.D. 1:1)	SHEET 1 OF	2
		TORONTO, ONTARIO CANADA O QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING N	NUMBER: 629-3W3	3-240-4N2	ISSUE
	YOUR CONNECTION TO QUA			PART NUME	IBER: 629-3W3	3-240-4N2	1

-55°C ~ 125°C

1000V AC rms





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

