



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 46.6              |
| B1  | 21.5              |
| B2  | 16.6              |
| C   | 43.3              |
| D   | 58                |
| E   | 66                |

| NO. | BESCHREIBUNG / DESCRIPTION           |
|-----|--------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN  |
| 3   | DICHTKÖRPER / GROMMET                |
| 4   | ENDRING / ENDRING                    |
| 5   | KONTAKTSTIFT/ CONTACT PIN            |
| 7   | ZYLINDERGHÄUSE / BARREL              |
| 9   | ÜBERWURFMUTTER / COUPLING NUT        |
| 10  | DICHTRING FRONT / FRONT SEALING RING |
| 12  | ENDGEHÄUSE / ENDBELL                 |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change  
Drawings illustrate normal insulator positioning

Material Specification:

|                     |                                 |
|---------------------|---------------------------------|
| Shell Material:     | Aluminium alloy                 |
| Shell Plating:      | Zinc cobalt, black (conductive) |
| Insulator Material: | CR-Elastomere                   |
| Contact Material:   | Copper alloy                    |
| Contact Plating:    | Hard silver                     |

all dimensions are in mm  
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
CUSTOMER



description CA3108E24-12P-B-A232  
Plug, 90°  
Endbell with clamp and bushing  
Solder Cup / Pin / Layout: 24-12

© All rights reserved. Reproduction or issue to third in any form  
whenever is only permitted with written authorization of ITT Cannon

page 1/1 revision 1730 14. May 19