

ATGBICS 100BASE-FX-MM-SFP-C network transceiver module Fiber optic 100 Mbit/s 1310 nm

Brand : ATGBICS

Product code: 100BASE-FX-MM-SFP-C

Product name : 100BASE-FX-MM-SFP-C



Huawei Compatible Transceiver SFP 100Base-FX 1310nm MMF 2km DOM

[ATGBICS 100BASE-FX-MM-SFP-C network transceiver module Fiber optic 100 Mbit/s 1310 nm:](#)

ATGBICS 100BASE-FX-MM-SFP 100Base-FX supports a distance of up to 2km over multi-mode fibre (MMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Huawei 100BASE-FX-MM-SFP= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



| Performance | | Features | |
|--|---------------|-----------------------------------|----------------|
| SFP transceiver type * | Fiber optic | Easy to install | ✓ |
| Maximum data transfer rate * | 100 Mbit/s | Country of origin | United Kingdom |
| Interface type * | SFP | Brand compatibility | Huawei |
| Single-mode fiber (SMF) supported | ✗ | Power | |
| Multi-mode fiber (MMF) supported | ✓ | Input voltage | 3.3 V |
| Fiber optic connector | LC | Maximum voltage | 4 V |
| SFP transceiver standard | FX | Power consumption (typical) | 1.3 W |
| Maximum transfer distance | 2000 m | Operational conditions | |
| Wavelength | 1310 nm | Maximum operating temperature | 70 °C |
| Ethernet LAN | ✓ | Operating temperature (T-T) | 0 - 70 °C |
| Ethernet interface type | Fast Ethernet | Storage temperature (T-T) | -40 - 85 °C |
| Copper ethernet cabling technology | 100BASE-FX | Operating relative humidity (H-H) | 5 - 85% |
| Digital Diagnostics Monitoring (DDM) | ✓ | Storage relative humidity (H-H) | 5 - 85% |
| Wavelength-division multiplexing (WDM) | ✗ | Weight & dimensions | |
| Features | | Width | 12.7 mm |
| Product colour | Silver | Depth | 55.9 mm |
| Housing material | Metal | Height | 7.62 mm |
| Plug and Play | ✓ | Weight | 19 g |
| Hot-Plug support | ✓ | Packaging data | |
| Hot-swap | ✓ | Number of products included | 1 pc(s) |
| | | Package type | Box |
| | | Technical details | |
| | | Sustainability certificates | RoHS |



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.