



Data sheet | Item number: 756-3101/040-020

Power cable; M12A socket; straight; 4-pole; Length: 2 m

www.wago.com/756-3101/040-020



Pin 1 ... 4: 0.75 mm²

1)	brown	_____
2)	white	_____
3)	blue	_____
4)	black	_____

Item description

Short description:

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



- PUR, halogen-free
- UL / CSA
- Suitable for drag chains
- Silicon- and CFC-free
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Data

Technical data

Connection type	M12 socket - free end
Pole number	4
Cable connection direction to mating direction	0°
Connector interface coding (cable/adapter) 1 1	A-coded
Cable length	2 m
PLC manufacturer	WAGO
Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Contact resistance	10 mΩ
Insulation resistance	1000 MΩ
Conductor resistance	≤ 26 Ω/km

Mechanical Data

Bending radius	10 x cable diameter (min.) for flexible application
Bending cycles	4 Mio.
Drag chain capability	yes
Sheathed cable diameter	6 ... 6.4 mm
Type code	Lif9YH-11YH 4x0.75 mm ²
Conductor configuration	Bare copper wire (40 x 0.15 mm)
Conductor insulation	PP9Y (halogen-free)
Housing material	TPU/TPU, black (~ RAL 9005)
Tightening torque	1 Nm
Weight	130 g

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Environmental requirements

Ambient (operating) temperature (dynamic)	-30 ... +80 °C
Ambient (operating) temperature (static)	-30 ... +80 °C
Protection type	IP67
Pollution degree	3/2 per IEC 60664-1

Commercial data

eCl@ss 10.0	27-06-18-01
eCl@ss 9.0	27-06-18-01
ETIM 8.0	EC001855
ETIM 7.0	EC003249
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4045454772383
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	ab3acad7-0109-4c0f-b9ec-17cf1a76e972
SCIP notification number (Belgium)	81493ad8-5fd7-46e7-97e9-08c4b515db5e
SCIP notification number (Bulgaria)	f3fa3127-7e86-4bf2-a003-ec5c0f8fc85a
SCIP notification number (Czech Republic)	8085b96a-9791-4bef-8b86-7a0d49b545d3
SCIP notification number (Denmark)	756ff04c-18cc-4ba3-bc18-87088de43724
SCIP notification number (Finland)	ca269dc9-9222-4dc7-8c37-38300a3e6e31
SCIP notification number (France)	c43e38b2-d295-4e02-b59a-bd3ead8ce482
SCIP notification number (Germany)	167d3f5b-b695-4c85-a63d-be65e47cd102
SCIP notification number (Hungary)	078a763d-c54b-4f82-9edc-7d4f543087df
SCIP notification number (Italy)	a44bc328-bc34-41f3-bd06-d5b43a49461a
SCIP notification number (Netherlands)	434b730c-7b16-4ef4-be63-02c7d2ddadd9
SCIP notification number (Poland)	bedc1eb3-59c3-44d5-ad29-fe023124a3f1
SCIP notification number (Romania)	cbb8e338-1ea2-4f92-af73-3dfeac2fc4ea
SCIP notification number (Sweden)	484a8cbc-cf35-4155-873d-2ed775a8127e

Subject to changes. Please also observe the further product documentation!


WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

System Description

I/O-SYSTEM – SPEEDWAY, General Product Information	pdf 1.1 MB	Download
--	---------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 756-3101/040-020	URL	Download
WSCAD Universe 756-3101/040-020	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-3101/040-020 Power cable; M12A socket; straight; 4-pole; Length: 2 m	URL	Download
--	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.