T 0			0	8 >	
A Z D D D D D D D D D D D D D D D D D D					4
			LAYOUT SHOWN AS EXAMP		3
	Keying Shown as example				
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal	-			
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	ØS 41.7 Max Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed		
-Durability : 500 Mating cycles			FR Not Listed 2 PN: 8D521W42SN 2		
-Delivered with Souriau contacts and Accessories			PIN. 0D321VV423N		
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 10-10-2016	First Release		
		ISS DATE	Latest modification - by	MOD	N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	TITLEAluminium Plug 8D series		
BASIC SERIES: 8D 5 - 21 W 42 SHELL TYPE : Plug with RFI Shielding	S N	SCALE -	General linear Tolerances: ±	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	ORI CONTACT TYPE : SOCKET	ENTATION : N (500 Matings)	WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission	
PLATING : W = Olive drab Cadmium		AYOUT : 21-42 FORMAT	SOURIAU DR		±T
	_	A3	8D521W425		<u>,</u>
H G	FEE	D	С	ВАА	

r	т	G	ات	m	D	0	
4		Contact Layout 42					
	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19					
ω							
	-					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recon	ducts wl either o nmenda
N						PN: 8D	Count FR 521
					A 10-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
_ _					SCALE NA	Genera 	Alumir al linear ances:
					FORMAT A3	SOU	RIAU
	Н	G	F	E	D AS	8D5	21W

