	т <u></u>	m	D	0	B	_
4	R 22.6 Max b b b b b b c c c c c c c c c c c c c	S				4
	Koving Sl	hown as example				
	CHARACTERISTICS	Connector dimension				
	-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	Dim Nominal A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum			Country FR	Jurisdiction & Control List Not Listed	2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D711W01PD			
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 01-10-2016 First Release			
_	-Mass : 18.17 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	MOD N° CUSTOMER DRAWING	<u> </u>
			TITLE Aluminium Receptacle 8D series			
<u> </u>	BASIC SERIES: 8D 7 - 11 W 01 P SHELL TYPE : Jam nut Receptacle	D	SCALE	General linear Tolerances: ±	NPRDS / PROJECT 859	1
	CONTACT TYPE : Standard Crimp Contact SOURIAU V			WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or		
	SHELL SIZE : 11 PLATING : W = Olive drab Cadmium	CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 11-01	FORMAT	SOURIAU D	communicated without permission RG N° SHEET	-
			A3	8D711W01		
	H G F		D	C	в і А	

Г	۲ G	т п		B			
	Contact Layout	Panel cutout					
4	01		JAM NUT RECEPTACLE (TYPE 7)	4			
_	1#12						
ω	11-01 Ctc X Y A 0 0		Dim Nominal B 19.59+0/-0.25 ØC 20.96+0.25/-0	3			
			due to a use of the Products the Specifications issued by eithe	any non-conformity or damage which does not comply with r of the Parties or by a third party dation, technical notice.)			
N			 Cou	ntry Jurisdiction & Control List R Not Listed 2			
			A 01-10-2016 First Release	PN: 8D711W01PD			
			ISS DATE Latest modification - by Designed By: Date:	MOD N°			
				um Receptacle 8D series			
→			SCALE General line NA Tolerances ±				
			SOURIAU WWW.SOURIAU	.COM SOURIAU it must not be reproduced or communicated without permission			
				U DRG N° SHEET NO1PD-C 2/2			
L	H G	F E	DC	BA			