

ATGBICS Mellanox MCP2m00-A001 Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 1m Passive

Brand : ATGBICS

Product code: MCP2M00-A001-C

Product name : Mellanox MCP2m00-A001 Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 1m Passive

Mellanox MCP2m00-A001 Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 1m Passive

[ATGBICS Mellanox MCP2m00-A001 Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 1m Passive:](#)

ATGBICS MCP2m00-A001 compatible 25GBase-CU SFP28 to SFP28 direct attach cable operates over passive copper with a cable length of 1m. It is suitable for short reach connection between two SFP28 ports in 25G interconnecting networking applications. Our product is built to the exact specification of Mellanox MCP2m00-A001= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; SFF-8402 and SFF-8432 and MSA SFP+ MSA SFF-8431. ATGBICS Mellanox MCP2m00-A001 Compatible SFP28 Direct Attach Copper Twinax Cable 25G SFP28 1m Passive. Cable length: 1 m, Connector 1: SFP28, Connector 2: SFP28, Data transfer rate: 25000 Mbit/s



| Features | | Features | |
|-------------------------|--------------------------|-----------------------------------|-------------|
| Product colour * | Black | Plug and Play | ✓ |
| Cable length * | 1 m | Certification | CE,FCC |
| Connector 1 * | SFP28 | Operational conditions | |
| Connector 2 * | SFP28 | Operating temperature (T-T) | 0 - 70 °C |
| Connector 1 gender * | Male | Storage temperature (T-T) | -40 - 80 °C |
| Connector 2 gender * | Male | Operating relative humidity (H-H) | 10 - 90% |
| Jacket material | Polyvinyl chloride (PVC) | Storage relative humidity (H-H) | 10 - 85% |
| Conductor material | Copper | Packaging data | |
| Ethernet interface type | 25 Gigabit Ethernet | Quantity per pack | 1 pc(s) |
| Networking standards | IEEE 802.3by | Technical details | |
| AWG wire size | 30 | Sustainability certificates | RoHS |
| Data transfer rate | 25000 Mbit/s | | |



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.