

TRIPP·LITE

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Fiber Optic - 10/100/1000 to 1000BaseLX SC Gigabit Multimode Media Converter, 2km, 1310nm

MODEL NUMBER: N785-001-SC









An economical way to extend the distance up to 2 Km (1.2 Miles) of remote Gigabit network nodes by converting Cat5/6 UTP Ethernet to Fiber Optic while still maintaining the existing infrastructure.

Description

Tripp Lite's N785-001-SC 10/100/1000 Gigabit Multimode Media Converter is an economical way to extend the distance (up to 2Km) of network nodes by converting Cat5/6 UTP cables to Fiber Optic. With advanced features such as selectable half or full duplex operation on the fiber port, 1300 nm wavelength, automatic MDI/MDI-X configuration and link fault pass-through, the N785-001-SC supplies superior signal quality and gives you ultimate network control. The N785-001-SC is compatible with both 62.5/125 and 50/125 multimode fiber cable.

Features

- Connect 10/100/1000 UTP Ethernet to 1000BaseLX Fiber Ethernet
- Auto MDI/MDI-X
- UTP port auto-senses network speed
- Fiber lengths up to 2Km
- 6 LED Function lights
- Uses 62.5/125 or 50/125 Multimode cable
- 3.75"L x 2.75"W x 1"H
- Wavelength: 1300nm
- RoHS Compliant
- Supports Multimode 50/125 cable up to 2km or 62.5/125 cable up to 400M

Specifications

Highlights

- Converts UTP Gigabit Ethernet to Fiber Optic
- Cost-effective solution for extending network distance up to 2 km
- Automatic MDI/MDI-X configuration
- Half or Full Duplex Operation
- Auto-Senses 10 / 100 / 1000
- Supports Multimode 50/125 cable up to 2km or 62.5/125 cable up to 400M

Package Includes

- N785-001-SC 10/100/1000 to 1000BaseLX Gigabit Multimode Media Converter
- External Power Supply with NEMA 1-15P Plug (Input: 110-265V, 50/60Hz, 0.2A; Output: 5V, 2A)
- Owners Manual





OVERVIEW	
UPC Code	037332153777
AC Adapter	Input: 110-265V, 50/60Hz, 0.2A; Output: 5V, 2A
PHYSICAL	
Color	Black
Shipping Dimensions (hwd / cm)	23.50 x 5.51 x 12.50
Shipping Dimensions (hwd / in.)	9.25 x 2.17 x 4.92
Shipping Weight (kg)	0.43
Shipping Weight (lbs.)	0.94
CONNECTIONS	
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	SC DUPLEX (FEMALE)
FEATURES & SPECIFICATIONS	
Technology	Cat5/5e; Cat6; Multimode
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies