

# TELEPHONE LINE PROTECTOR, 500 A 8/20 MS MAX DISCHARGE CURRENT (IMAX), PER MODE

## CATALOG NUMBER

**SLP1RJ11**



## CERTIFICATIONS



## FEATURES

RJ11 sockets provide simple plug-in connection for 4 or 6 position RJ plugs

Includes patch cord and adhesive mounting strips

Provides both L-L and L-PE protection modes for comprehensive protection

Automatic over-current protection

## PRODUCT ATTRIBUTES

Max Continuous Operating Voltage (Uc): 280 V

Max Discharge Current (Imax), Per Mode: 500 A 8/20  $\mu$ s

Voltage Protection Level (Up), T-R: 110 V

Voltage Protection Level (Up), T/R-G: 500 V @ 125 A

Rated Load Current (IL): 160 mA

Connection Type: RJ11

Ground Lead Length: 6"

Lead Size: #18

Temperature: -40 to 149 °F

Depth (D): 1.100"


Height (H): 1 1/2"

Width (W): 3.060"

Unit Weight: 0.110 lb

Certification Details: UL® 497A

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

### Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

### Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

### APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:  
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**