

## Protect It! 9-Outlet Surge Protector with 4 Rotating Outlets, 6 ft. Cord, 2160 Joules, Tel/DSL/Fax Protection, Black

MODEL NUMBER: TLP906RTEL



### Highlights

- 9 NEMA 5-15R outlets, including 4 rotating outlets
- 2160-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- Automatic shutoff protects against dangerous overloads
- 6 ft. AC power cord with NEMA 5-15P plug

### Package Includes

- TLP906RTEL Protect It!® 9-Outlet Rotating-Outlet Surge Protector
- Owner's manual

Surge protector with rotating outlets safeguards your PC, printer, scanner, router, phone, fax, modem and other home/office electronics against dangerous surges, spikes and line noise.

### Description

Perfect for your home or office workstation, the TLP906RTEL Protect It!® 9-Outlet Rotating-Outlet Surge Protector features a surge protection rating of 2160 joules to defend your sensitive electronic components against even the strongest surges and spikes.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP906RTEL protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

Your devices plug into nine NEMA 5-15R outlets, four of which rotate 90 degrees on two bars of two outlets each to allow greater flexibility in placing connected devices or accepting bulky transformers without blocking adjacent outlets. RJ11 jacks allow connection of telephone/fax/modem equipment, which is also protected from surges.

A lighted power button with integrated 15A circuit breaker protects all outlets and automatically shuts down connected equipment in case of overload. Diagnostic LEDs confirm your wall outlet is properly grounded and your connected equipment is protected.

The six-foot AC power cord with NEMA 5-15P plug allows the TLP906RTEL to reach distant outlets. A cable manager on one end of the black plastic housing holds loose power cords in place to relieve clutter.

### Features



**2160-Joule Surge Protection for Home or Office Electronics** Protects your computer, printer, scanner, router, modem and other electronics against even the strongest surges and spikes Recommended for any desktop, network or home electronics application requiring AC line protection Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss Exceeds IEEE 587 Category A and B surge suppression specifications

**9 Outlets Accept Wide Range of Electronic Devices** 9 NEMA 5-15R AC outlets accept most computers and peripherals 4 outlets are placed on 2 rotating bars of 2 outlets each to accommodate bulky transformers without blocking other outlets

**Telephone/DSL Protection** RJ11 jacks (1 input/1 output) protect phone/fax/modem equipment from surges and spikes

**Premium Safety Features** On/off switch provides one-touch control over connected equipment Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required Diagnostic LEDs confirm grounding and protection status at a glance Conforms to current UL 1449 3rd Edition safety standards

**Fits Effortlessly Into Your Workstation** 6 ft. AC power cord with NEMA 5-15P plug conveniently reaches distant outlets Cable manager holds power cords in place to prevent cable clutter Black plastic housing designed for long life

**Backed by Tripp Lite's Ultimate Lifetime Insurance** \$150,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

## Specifications

OVERVIEW	
UPC Code	037332206992
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(9) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(4) Yes
Outlet Orientation	Single row of 5 fixed outlets and 2 rotating bars with 2 outlets each
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input Cord Gauge Type	14 gauge; SJT
Voltage Compatibility (VAC)	120
Maximum Surge Amps	144000
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	6
Right-Angle Plug	No
Input Cord Length (m)	1.83



Integrated Cord Clip	No
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Diagnostic LED(s)	Yes
Switches	Combination AC circuit breaker and push button red illuminated on/off power switch
Diagnostic LED Details	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
<b>SURGE / NOISE SUPPRESSION</b>	
AC Suppression Joule Rating	2160
AC Suppression Response Time	< 1 ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
Clamping Voltage (RMS)	150
UL1449 Let Through Rating	330/400/400
EMI / RFI Filtering	Up to 40 dB
Auto Shut-Off	Yes
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	12.00 x 7.09 x 2.17
Shipping Dimensions (hwd / cm)	30.48 x 18.01 x 5.51
Shipping Weight (lbs.)	1.66
Shipping Weight (kg)	0.75
Unit Dimensions (hwd / in.)	10.02 x 3.35 x 1.94
Unit Dimensions (hwd / cm)	30.5 x 29.5 x 37.8
Unit Weight (lbs.)	1.48
Unit Weight (kg)	0.67
Material of Construction	Plastic
Integrated Keyhole Mounting Slots	No
Housing Color	Black
Receptacle Color	Black; gray
Color (AC Line Cord)	Black
Color	Black



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

Anti-Microbial Protected	No
<b>SPECIAL FEATURES</b>	
Additional Information	Pair of phone line output jacks serve as a line splitter to enable the protection of two devices sharing a single dialup phone line
<b>CERTIFICATIONS</b>	
UL1449 3rd Edition (AC Suppression)	UL1449 3RD EDITION
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
Canada	cUL
Industry Canada (Communications)	Industry Canada
Approvals	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$150,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>