



## Main

|                           |                      |
|---------------------------|----------------------|
| Range of Product          | Harmony 9001SK       |
| Product or Component Type | Head for push-button |
| Device short name         | 9001SK               |
| Bezel material            | Plastic              |

## Complementary

|                                 |                                  |
|---------------------------------|----------------------------------|
| Mounting diameter               | 1.18 in (30 mm)                  |
| CAD overall width               | 1.81 in (46 mm)                  |
| CAD overall height              | 1.77 in (45 mm)                  |
| CAD overall depth               | 2.72 in (69 mm)                  |
| Net Weight                      | 0.21 lb(US) (0.095 kg)           |
| Operating position              | Any position                     |
| Shape of signaling unit head    | Round                            |
| Type of operator                | Spring return                    |
| Operator profile                | Green mushroom Ø 57 mm, unmarked |
| Mechanical durability           | 5000000 cycles                   |
| Operator additional information | Snap-in plastic                  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TC   |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)   |
| Electrical shock protection class     | Class II IEC 61140   |
| IP degree of protection               | IP66 IEC 60529   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X                               |
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>JIS C 852<br>UL 508 |
| Product Certifications                | UL listed file E78403 CCN NKCR<br>CSA LR25490 class 3211 03<br>UL 508<br>NEMA                                  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                      |                               |
|----------------------|-------------------------------|
| Vibration resistance | 7 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance     | 50 gn IEC 60068-2-27          |

## Ordering and shipping details

|                       |                     |
|-----------------------|---------------------|
| Category              | 21429-9001 SK,SKY   |
| Discount Schedule     | CS1                 |
| GTIN                  | 785901042839        |
| Nbr. of units in pkg. | 1                   |
| Package weight(Lbs)   | 8.00 oz (226.796 g) |
| Returnability         | No                  |
| Country of origin     | MX                  |

## Packing Units

|                        |                      |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE                  |
| Package 1 Height       | 7.62 in (19.355 cm)  |
| Package 1 width        | 3.00 in (7.62 cm)    |
| Package 1 Length       | 19.35 in (49.161 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|