



GEN. ST.	01	02	03	04	05	06	07	08	0D	50	60	70	80	90																	
INT. ST.	10	11	12	13	14	18	20	31	32	33	34	38	39	40	42	43	44	45	46	48	56	70	72	73	75	76	81	82	83	84	88


REV.	DATE	DESCRIPTION	BY	C'K'D'



MATERIAL
POLYAMIDE 4.6 / UL94-V2 AT 0.9MM / COLOR: NATURAL

PERFORMANCE CHARACTERISTICS
 OPERATING TEMPERATURE: -55°C TO 150°C
 INSULATION RESISTANCE: 5000 MΩ MIN.
 TEST POTENTIAL : 2000 VAC
 DURABILITY : 500 CYCLES

- NOTES**
- CONNECTOR ACCEPTS TRIM TRIO FORMED, MACHINED AND SUBMINIATURE COAXIAL SOCKET CONTACTS (4x) AND POWER CONTACTS DIAM. 2.4 (8x) CONTACTS TO BE ORDERED SEPARATELY; REFER TO TT-CATALOG AND 8P-CATALOG.
 - RAISED CONTACT MARKING ON BOTH: MATING AND WIRING FACE.
 - CONNECTOR DELIVERED WITH MOULDED-ON HOODS. HOODS MUST BE CUT AWAY BY CUSTOMER.
 - CATALOG NUMBER OF COUNTERPART : SMS12PDH2NA.



CATALOG NUMBER	QUANTITY OF CONTACT CAVITIES	QUANTITY OF DISCRIMINATION CAVITIES	DIMENSIONS IN MM			
			A	B	C	D
SMS12RDH2NA	12 (8+4)	0	40.7	25.1	72.0	16.2

RELEASED FOR TOOLDESIGN

1DEC ±0,2 1DEC 2DEC ±0,1 2DEC ANGLES ±1° HOEKEN	APPR. DRAFT CHECKED	DATE 14-04-99	SIGN. K. NIETVELT
WE RESERVE THE RIGHT TO CHANGE DIMENSIONS OR REQUIREMENTS WITHOUT PRIOR NOTICE.	PROD. MGR. PR. ENG. MGR. PR. MGT. MGR.		
ALL DIMENSIONS IN MM ALLE AFMETINGEN IN MM	REFERENCES/REFERENTIES		

QIKMATE RECEPTACLE 12POS. WITH 8POWER CAVITIES

CAT. No. SMS12RDH2NA

SOURIAU
Route Nationale 23
72470 CHAMPAGNE

NOT EXPORT CONTROLLED

BS, D , 202648 , 002 , 1B
DRAWING No. CUSTOMER DRAWING

THIS IS OUR EXCLUSIVE PROPERTY. IT IS NOT TO BE COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY, NOR USED FOR MANUFACTURING WITHOUT OUR WRITTEN CONSENT, AND HAS TO BE RETURNED TO US IN CASE OF NO USAGE

DIT IS ONZE EIENDOM EN MAG NOCH NAGEMAAKT, HERDRUKT, OVERGEMAAKT AAN DERDEN, NOCH VOOR FABRIKATIE GEBRUIKT WORDEN, ZONDER ONZE SCHRIFTELIJKE TOELATING. BIJ NIET GEBRUIK IS TERUGZENDING VERPLICHT.